

# Станки для и ки ар ат р и рои водства ско CS 440/460, CS 40/50 ни ски аракт ристики

## По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

# CS 440-460

# CS 40-45

## AUTOMATIC SHAPING

The automatic double head benders belonging to the "CS 440-460" series are designed for production of stirrups and large shapes bended clockwise or counter-clockwise on both sides.

The bending sequences are controlled in full automatic mode without requiring any intervention by the operator during the working cycle, so granting high productivity along with quality of finished products.



## VERSATILITY AND PRODUCTIVITY


All CS Series double head benders can be installed in different configurations fitting the specific production requirements. Along with versions having one mobile head at whatever side, the unit is also available in configuration with two mobile heads capable to work simultaneously and so assuring very high productivity.

The 440-460 version is a further step ahead being equipped with an exclusive retractable pin system which allows full bending ( $\pm 180^\circ$ ) on both directions on the same piece.

# Bend with no limits

## BENDING PINS UNDER RULES

The automatic double head benders belonging to the "CS 460" series are equipped with an automatic device for the expulsion of the central bending pin which facilitates the replacement. Shaping centers "CS" uses a full set of bending pins complying to the international standards.



The "CS 440-460" automatic double head bender is equipped with an exclusive system designed to bend clockwise and counter-clockwise at full  $\pm 180^\circ$  angle without any limitation, therefore expanding the range of shapes that can be processed on the unit.

## REAL 180° CLOCKWISE AND COUNTER-CLOCKWISE

Bending is executed by mean of a retractable lateral bending pin. The retractable lateral bending pin works in a very simple and efficient manner. After having made the first two bends on counter-clockwise,  $-180^\circ$  ① e  $-90^\circ$  ②, the lateral bending pin retracts (↓) ③, and re-position itself on the opposite side of the processed bar to execute the next clockwise bend,  $+45^\circ$  ④. The whole sequence is very fast and performed in full automatic mode.

## AUTOMATIC CONTRASTS

The contrast clamps (CS 460) are actived automatically during the working cycle according to the shape under production process assuring the best product quality.





## LIFTING AND FEEDING SYSTEM

The front conveyor is equipped with rubber rollers and with a **lifting arms system** specifically designed to feed the bending station, while helping the machine operator in **selecting and picking of the bars** to be processed.



## BAR ALIGNMENT


A retractable endstop, positioned on the bender, allows a perfect **bar alignment**, ensuring the **correct measurement tolerances**.




## SECURE LOCK

The CS version with **two mobile heads** is equipped with a **central clamp hydraulically driven**. It ensures the **firm locking and the support** of the bars while the two heads are moving along the unit and performing the bending sequence.


## VERSATILITY AT YOUR SERVICE: CS440 CS460- CS40-45



CS440-460 o CS40-45 with fixed machine on the Left Side.



CS440-460 o CS40-45 with fixed machine on the Right Side.



CS440-460 o CS40-45 with two mobile machines.

# WORLD SYSTEM Controllo Totale




The P.C.I. System through an interface "user friendly" organized by a "Windows" structure provide the following functions:

- Programming of various types of shapes with up to a maximum of 30 sides and 29 angles (8 sides and 7 angles CS40-45 model).
- The software controls the bending cycle of the two units, depending on the diameter of the bars and bending pins lowering the time setting of the machine.
- Stores up to a maximum of 99 different forms of shaped.
- Display of various forms-programmed.
- Control and variation of the various work cycles.
- Displayed simulation of the work cycles.
- Storage summary of data daily production.
- Check function of all units of the machine.
- Displaying help messages to facilitate all operations. (CS 440-460 model).

- The unit is already prepared for any downloading of data from external computer via RS 232 link, or with a barcode reader.
  - Electronic programmer unit integrated (optional) on the two benders which enables the use of this units as an independent machine.
- This control unit, through a digital keyboard, allows programming up to 20 different angles that are executed sequentially.



Control panel for CS440-460



## AUTOMATIC UNLOADING SYSTEM

- The **shaped products** are **unloaded automatically** through a system that uses **three lifting devices**, which act simultaneously. This will eliminate unnecessary effort by the operator.



## CHAIN FEEDER



- 
- The **chain feeder** is a unit that collects, transports and deposits the bars cut to size by creating an efficient **intermediate storage station**. (OPTIONAL)

## DOUBLE ROLLER CONVEYOR TRANSPORT/COLLECTING CARRIAGE



- 
- The **second motorized roller conveyor**, complete with lateral discharge, can increase the storage capacity. (OPTIONAL)

## BIDIRECTIONAL BENDING FOR CS40-45



- 
- Centers shaping CS 40-45 can be equipped with a set of center and lateral pins for bidirectional bends. (OPTIONAL)

## LARGE RADII BENDING PINS



- 
- Large radii bending pins set is available with maximum diameter up to 500 mm. (OPTIONAL)

## TECHNICAL AND PRODUCTION CHARACTERISTICS

													
	REBAR	CS 40 SX		CS 45 SX		CS 440 mono-directional		CS 440 bi-directional		CS 460 mono-directional		CS 460 bi-directional	
	n° 1 bar with Ø	40 mm	#11	45 mm	#14	40 mm	#11	32 mm	#10	45 mm	#14	40 mm	#11
	n° 2 bars with Ø	32 mm	#10	34 mm	#10	32 mm	#10	28 mm	#9	36 mm	#11	32 mm	#10
	n° 3 bars with Ø	26 mm	#8	26 mm	#8	26 mm	#8	24 mm	#8	32 mm	#10	28 mm	#8
	n° 4 bars with Ø	20 mm	#6	20 mm	#6	20 mm	#6	20 mm	#6	28 mm	#8	22 mm	#7
	ANGOLO DI PIEGA												
	massimo	180°											
	VELOCITÀ DI TRASLAZIONE												
		0.7 m/s - 2.30 fps					0.8 m/s - 2.62 fps						
	VELOCITÀ DI PIEGA												
		5,6 ÷ 11,2 rpm					4 ÷ 12 rpm						
	DIAMETRO PERNI												
	minimo	30 mm - 1-1/4"			40 mm - 1-5/8"								
	massimo (altre misure su richiesta)	250 mm - 10"			250 mm - 10"		250 mm - 10"		200 mm - 8"		250 mm - 10"		200 mm - 8"
	VIA A RULLI DI MISURA												
	larghezza massima (altre misure su richiesta)	1005 mm - 39 9/16"											
	POTENZA INSTALLATA												
	massima (altre misure su richiesta)	24,4 kW - 32.7 hp					26 kW - 34.8 hp				28 kW - 37.5 hp		
Note: #6 = 3/4" ; #8 = 1" ; #9 = 1-1/8" ; #10 = 1-1/4" ; #11 = 1-3/8" ; #14 = 1-3/4"													

Алматы (7273)495-231  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89  
Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Россия (495)268-04-70

Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Липецк (4742)52-20-81  
Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Пермь (342)205-81-47  
Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Симферополь (3652)67-13-56  
Казахстан (7172)727-132

Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Тверь (4822)63-31-35  
Томск (3822)98-41-53  
Тула (4872)74-02-29  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Ярославль (4852)69-52-93

**По вопросам продаж и поддержки обращайтесь:**