Focus ни ски аракт ристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Россия (495)268-04-70

рсток (423)249-28-31 Красноярск (391)204-63-61 ад (844)278-03-48 Курск (4712)77-13-04 (8172)26-41-59 Липецк (4742)52-20-81 к (473)204-51-73 Магнитогорск (3519)55-03-13 нбург (343)384-55-89 Москва (495)268-04-70 б (4932)77-34-06 Мурманск (8152)59-64-93 (3412)26-03-58 Набережные Челны (8552)20-53-41 (395)279-98-46 Нижний Новгород (831)429-08-12

Киргизия (996)312-96-26-47

Казань (843)206-01-48

Калуга (4842)92-23-67

Киров (8332)68-02-04

Кемерово (3842)65-04-62

Краснодар (861)203-40-90

Калининград (4012)72-03-81

Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56

Казахстан (7172)727-132

Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93

Focus **12-13-14-16**

A NEW GENERATION

The FOCUS 12–13–14–16 are the ideal solution in the field of automatic coil stirrup benders for its ease of use and high performance.

Flexibility, productivity and product quality are always guaranteed.

a complete array of accessories, able to satisfy the

widest range of productive requirements.



The AFS system guarantees perfect straightening with flat stirrups.

YES!

QUALITY AND PRODUCTIVITY

The FOCUS 12-13-14-16 are a user friendly automatic stirrup bender that provides superior quality of finished products.

The combined action of an exclusive series of patented devices minimizes the time for setup adjustments and reduces drastically the amount of discarded products.

A drive and control system, based on the latest generation technology, grants to reach unparalleled levels of productivity per hour.



AN INNOVATIVE SOLUTION

The AFS is a straightening system that eliminates the effect of the wire rotation on its own axis. Therefore, closed stirrups and straight bars can always be produced. The independent control of the traction on two wires, as well as the increased surface of contact with the large infeed wheel, eliminates any difference in length between the two wires.

Thanks to this design and to the consequent lower pressure applied on the steel material, the coil ribs are far less deformed by the straightening process. The lifetime of the infeed roller themselves is about 8 times longer than in case of traditional straightening methods.









The twisting of the wire during the pulling phase creates open stirrups.



The combined functions of the AFS system and the straightening control software, provides a fast and precise setting of all the rollers (available on FOCUS 14–16).



SAFETY AND ERGONOMICS



With the system it is always granted to obtain closed stirrups, thus eliminating the typical and dangerous manual operation during the bending process by operator.

WORLD SYSTEM: TOTAL CONTROL



- MEP Industrial PC "World System" operator control panel is comprised of:
- LCD screen for the user friendly visualization of all data.
- Compact, "embedded" microprocessor with low power consumption.
- Input /Output and Control Axes electronic card with protection against short circuit and overload.

• The custom software developed by MEP allows:

- Data input with graphic visualization of programmed and pre-memorized shapes.
- Saving of 500 positions in memory.
- Control of all speed parameters in execution via a potentiometer.
- Saving and archiving of data relative to work cycles and generation of daily production statistics (diameters processed, and daily fabricated weights by diameter).
- "Active diagnostic" system for a constant efficiency check of all machine devices.
- Interface compatible with optical bar code reader through RS 232 port.
- Automatic operating speed reduction based upon the diameter of the stirrup.

QUALITY DECOILING



 Decoilers equipped with an automatic braking system monitored by the control panel according to the work cycle.



 Spacer for the use of spooled or rewound coils. (OPTIONAL)

ACCESSORIES



 Motorized pre-feeding roller, for the insertion of the wires.



• Winch equipped with clamping device for the wire end to be pulled.



• Supporting and collecting unit for the production of straight bars and bars bent at one end.



Bender supplied with central bending tools in compliance to the international standards

Exclusive MEP design, designed to facilitate the overlapping and the guiding of the external wire with respect to the internal one during the bending phase. This means that complex or even very small stirrup can be realized with two wires simultaneously.

TECHNICAL AND PRODUCTION CHARACTERISTICS

	SINGLE STRAND PROCESSING WIRE DIAMETER	FOCUS 12	FOCUS 13	FOCUS 14	FOCUS 16
	cold drawn, hot rolled, smooth or ribbed wire	Ø 4 - Ø 12 mm #2 - #4	Ø 4 - Ø 13 mm #2 - #4	Ø 6 - Ø 14 mm #2 - #4	Ø 6 - Ø 16 mm #2 - #5
	$\label{eq:fy} \begin{array}{lll} \text{fy} = 600 \text{ N/mm}^2 & - & \text{ft} = 700 \text{ N/mm}^2 \\ \text{(other loads upon request)} \end{array}$				
	DOUBLE STRAND PROCESSING WIRE DIAMETER				
	cold drawn, hot rolled, smooth or ribbed wire	Ø 4 - Ø 10 mm #2 - #3	Ø 4 - Ø 10 mm #2 - #3	Ø 6 - Ø 13 mm #2 - #4	Ø 6 - Ø 13 mm #2 - #4
	$\label{eq:fy} \begin{array}{lll} \text{fy} = 600 \text{ N/mm}^2 & - & \text{ft} = 700 \text{ N/mm}^2 \\ \text{(other loads upon request)} \end{array}$				
	SQUARE STIRRUP DIMENSIONS				
	minimum with Ø 4-6 mm wire (optional bending pin)	50 mm x 50 mm - 2" x 2" (Ø 4) 60 mm x 60 mm - 2 1/2" x 2 1/2" (Ø 6)			
	maximum if clockwise	1000 mm x 1000 mm - 3-3" x 3-3"			
	maximum if counterclockwise (with eventual optional cover extension)	2000 mm x 2000 mm - 6-7" x 6-7"			
	LENGTH OF STRAIGHTENED AND CUT-TO-LENGTH BAR				
	minimum	5 mm - 3/16"			
	maximum (if equipped with optional supporting guide; other sizes upon request)	12000 mm - 39-4"			
	CENTRE FORMING TOOLS DIAMETER				
	minimum	12 mm - 1/2"			
	maximum (other sizes upon request up to 62 mm - 2 1/2")	48 mm - 2"	52 mm - 1 31/32"	56 mm - 2 1/8"	62 mm - 2-1/2"
	MAXIMUM DISTANCE BETWEEN CENTRAL BENDING PIN AND THE GROUND				
	standard	1300 mm - 4-3"			
	optional upon request	> 1300 mm - > 4-3"			
<u>C</u>	OPERATING TEMPERATURE				
	standard	-5° C / +40° C - 23° F / 104° F			
	optional upon request	-15° C / +55° C - 5° F / 131° F			
S	INSTALLED POWER				
	maximum (other sizes upon request)	20 kW 26.6 hp	27 kW 36 hp	35 kW 46.6 hp	35 kW 46.6 hp
THE PLANT DOES NOT REQUIRE COMPRESSED AIR.					
fy: max. unit yield point - ft: max. tensile strength					
Note: #2 = 1/4" ; #3 = 3/8" ; #4 = 1/2"					

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Россия (495)268-04-70 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Липецк (4742)52-20-81 Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12

Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56

Казахстан (7172)727-132

Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93

Смоленск (4812)29-41-54

Ставрополь (8652)20-65-13

Сочи (862)225-72-31

mpa@nt-rt.ru || https://mepgroup.nt-rt.ru/